 F1060031 Matte Black

Bellhop Table ONLINE EXCLUSIVE

Designed by Edward Barber and Jay Osgerby, 2018




2.5W - 151lm - 2700K

Rechargeable direct light table lighting device. Base and dome in coloured PC. Diffuser in Opaline injection moulded photo-engraved PC. 24-hours' autonomy, charging via Micro-USB-C. Push-button switch positioned on the base provides the 4-step dimmer function. Battery status indicator positioned under the base. USB-C charging cable included, useful length 120cm.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

EAN	8059607047033
Mounting	Table
Environments	Indoor dry location
Light Source Type	LED
LED type	LED Module
Power (W)	2.5
System flux (lm)	151

Physical


Colour	Matte Black
Length (mm)	210
Net weight (kg)	1.3
Package volume (m3)	0.01
IP internal	20

Download


- [Mounting instructions](#)  PDF
- [Spare Parts](#)  PDF

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class C



Non-replaceable light source



Replaceable control gear by an end-user



Photometric

Lighting type	Direct
Light distribution	Roto symmetric
CCT (K)	2700

Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	100-240/5
Driver	Remote included
Dimmable	Yes
Dimming type	Electronic 5V
Dimming interface	Dimmer Integrated
Plug type	Type G, Type A, Type C
Batteries inside	Yes
Battery type	LI-PO
Charging max power	14
Charging min time	3h - 0% to 100%
Charging socket/connector	USB-C

Spare Parts



01. Power charger with electrical
cable & plugs

RF1035109

DOWNLOAD



RF1035109

Power charger with electrical
cable & plugs